

JTek JURNAL TEKNOLOGI
Fakultas Teknologi Industri Universitas Jayabaya

VOLUME 11, NO 1



NOVEMBER 2023

[wwwhttp://jurnalftijayabaya.ac.id](http://jurnalftijayabaya.ac.id)

ISSN : 1693-0266 (CETAK)
2654-8666 (ONLINE)

[Home](#) > [About the Journal](#) > [Editorial Team](#)

EDITORIAL TEAM

EDITOR-IN-CHIEF

[Dr.Ir.Wike Handini,MT.](#)

MANAGING EDITOR

[lukman Nulhakim. S.T., M.Eng.](#)

EDITORIAL BOARDS

[Dody Guntama.S.T.,M.Eng.](#), Indonesia
[Dr.Yeti Widaywati,ST.,M.Si.](#), Fakultas Teknologi Industri Universitas Jayabaya
[rika novita wardhani](#), Indonesia
[ratri ariatmi N](#), Indonesia
[syahbuddin syahbuddin](#), Teknik Mesin, Universitas Pancasila, Indonesia
[Agus Budi Djatmiko](#), Program Studi Teknik Mesin Fakultas Teknologi Industri Universitas Jayabaya, Indonesia
[Herlina Wahab](#), Indonesia
[Farid Thalib](#), Universitas Gunadarma

Fakultas Teknologi Industri Universitas Jayabaya
Jalan Raya Bogor Km. 28,8 Cimanggis, Jakarta Timur Indonesia
Telp. 021-8714823,8722485, Fax.021-87707720, Kotak Pos 4174
Email: jurnalteknologi@ftjayabaya.ac.id

JURNAL TEKNOLOGI INDEXED BY:



Copyright of Jurnal Teknologi

(ISSN 1693-0266 (Printed), ISSN 2654-8666 (Online)).



[View My Stats](#)

Accredited
SINTA 4



Article Template



[DEWAN EDITORIAL](#)

[PROSES PEER REVIEW](#)

[FOKUS DAN RUANG LINGKUP](#)

[ETIKA PUBLIKASI](#)

[INDEKSASI](#)

[HAK CIPTA](#)

[FREKUENSI TERBITAN](#)

[PETUNJUK PENULIS](#)

[KONFERENSI KAMI](#)

USER

Username

Password

Remember me

Video Tutorial

Tutorial Registrasi & s



[Registrasi dan Submit Jurnal Teknologi](#)

Tutorial review Jurnal



[Tutorial Review Jurnal](#)

[JOURNAL CONTENT](#)

[Home](#) / [Archives](#) / Vol. 11 No. 1 (2023): JURNAL TEKNOLOGI

Vol. 11 No. 1 (2023): JURNAL TEKNOLOGI



VOLUME 11, NO 1



DOI: <https://doi.org/10.31479/jtek.v11i1>

Published: 2023-11-28

Articles

Rancang Bangun Sistem Pengatur suhu dan Kelembaban untuk Ruang Budidaya Jamur Tiram Berbasis IoT

Ganis Sanhaji, Ikbal Nurfaiah, Riski Ba'ti Anbali

1-14

[PDF](#)

Pengembangan Purwarupa Sistem Monitoring dan Proteksi Logam Menggunakan Metode Sacrificial Anode Cathodic Protection Berbasis Internet of Things (IoT)

Rafi Ferdiansyah Raihan, Reza Kelana Bakti, Sekhah Ulyana, Dien Rahmawati, Faisal Budiman

15-24

[PDF](#)

Survei Volume Lalulintas Dengan Internet Of Thing Yolo-V5

Darmadi Darmadi, Pratikso Pratikso, Mudiyo Rachmat

25-35

[PDF](#)

Potensi Energi Terbarukan di Sumatra Tahun 2020-2050 Menggunakan Long-range Energy Alternatives Planning System (LEAP)

Abeth Novria Sonjaya, Dolar Marpaung, Sri Wiji Lestari, Nur Witdi Yanto, Yeti Widyawati
36-57



Pembuatan Biokompatibel Komposit dari Nano Hidroksiapatit Berbahan Dasar Cangkang Keong Sawah (Pila ampullacea) dengan Kombinasi Biopolimer PVA (Polyvinyl Alcohol) sebagai Bahan Dasar Pembuatan Suture Anchor

Yasmin Inayah, Agnes Surya Putri Anggraeni, Achmad Dwitama Karisma
58-66



Pengaruh Waktu dan Suhu pada Ekstraksi Keratin Bulu Ayam sebagai Bahan Baku Filler Pada Pembuatan Edible Film berbasis Pati Singkong

Alif Salma Nurillah, Gracella Audrey Toar, Lily Pudjiastuti
67-77



Uji Kekuatan Mekanik Filamen 3d Printing Suture Anchoring Screw Berbasis Biokomposit Hydroxyapatite-Polycaprolactone (HAp-PCL)

Muhamad Bahrul Ulum, Muhammad Rizky Aulia Susilo, Achmad Dwitama Karisma
78-84



Purifying Crude Glycerol from Biodiesel Production for Sustainable Energy Solutions

Herliati Rahman
85-99



Perencanaan Turbin Pelton Untuk Pembangkit Listrik Tenaga Mikrohidro Kapasitas 100 watt

Abeth Novria Sonjaya, Ferry Setyo Nugroho, Muhammad Vergiant Vindiawan
100-109



Perancangan Tabung Motor Roket RX 250 Akibat Laju Perpindahan Panas dan Tekanan

fauzhia rahmasari, Agus Budi Djatmiko, Aji Digdoyo, Erma Yuniaty, Nani Kurniawati, I Nyoman Artana, Bagas Setiohadi
110-119



Purifying Crude Glycerol from Biodiesel Production for Sustainable Energy Solutions

Herliati Rahman

Chemical Engineering, Faculty of Industrial Technology, Jayabaya University

herliati@ftijayabaya.ac.id

Abstrak

Produksi biodiesel telah menjadi bagian penting dari upaya global untuk mengganti bahan bakar fosil dengan sumber energi terbarukan. Namun, salah satu masalah yang dihadapi dalam produksi biodiesel adalah peningkatan produksi gliserol sebagai produk samping. Gliserol, atau crude glycerol (CG), umumnya dihasilkan dalam jumlah signifikan dan perlu dikelola dengan bijaksana. Artikel ini membahas potensi pemanfaatan gliserol dari produksi biodiesel sebagai bahan baku untuk produksi bioetanol. Bioetanol adalah salah satu bahan bakar terbarukan yang ramah lingkungan. Penelitian ini membahas potensi transformasional gliserol dari produksi biodiesel sebagai bahan baku untuk produksi bioethanol. Beberapa kemajuan dalam teknologi pemisahan untuk memurnikan CG seperti distilasi, perlakuan kimia, dan filtrasi membrane atau ion exchange telah mendorong pengembangan konversi CG menjadi bioethanol. Dengan menggunakan metode yang telah disebutkan, kualitas crude glycerol (CG) dapat ditingkatkan dari 50% menjadi sekitar 90–95% berat. Selain itu, kemajuan dalam rekayasa genetika membuka pintu bagi pengembangan mikroorganisme yang lebih efisien dan produktif. Hal ini menciptakan peluang besar untuk mengurangi limbah, mendukung keberlanjutan sumber daya, dan mengurangi ketergantungan pada bahan bakar fosil melalui pemanfaatan gliserol sebagai bahan baku bioetanol. Konversi gliserol menjadi bioetanol merupakan langkah menuju energi terbarukan yang lebih berkelanjutan dan ramah lingkungan.

Kata Kunci: *Bioetanol, Energi terbarukan, Keberlanjutan, Rekayasa genetik*

Abstract

The production of biodiesel has become a crucial part of the global effort to replace fossil fuels with renewable energy sources. However, one of the challenges faced in biodiesel production is the increased production of glycerol as a by-product. Glycerol, or crude glycerol (CG), is generally produced in significant quantities and needs to be managed wisely. This article discusses the potential utilization of glycerol from biodiesel production as a raw material for bioethanol production. Bioethanol is one of the environmentally friendly renewable fuels. This research explores the transformative potential of glycerol from biodiesel production as a raw material for bioethanol. Progress in separation technology to purify CG, such as distillation, chemical treatment, and membrane filtration or ion exchange, has driven the development of CG conversion into bioethanol. Using the mentioned methods, the quality of crude glycerol (CG) can be improved from 50% to approximately 90–95% by weight. Furthermore, advancements in genetic engineering open the door to the development of more efficient and productive microorganisms. This creates significant opportunities to reduce waste, support resource sustainability, and decrease dependence on fossil fuels through the utilization of glycerol as a raw material for bioethanol. The conversion of glycerol into bioethanol is a step towards more.

Keywords: *Bioethanol fuel, Genetic engineering, Renewable energy, Sustainability*

Introduction

In this decade, the issue of declining availability of fossil fuels worldwide has become a prominent topic receiving widespread attention [1]–[3]. This is due to various factors leading to a common discourse on energy crises and sustainability. Global communities have grown heavily reliant on fossil fuels such as oil, coal, and natural gas to meet their energy needs. This encompasses the use of fossil fuels in transportation, electricity generation, and industry [4]–[8]. As a result, the reserves of fossil fuels, the primary source of conventional energy, continue to deplete alongside rising global demand. Furthermore, excessive use of fossil fuels has resulted in adverse environmental impacts, including greenhouse gas emissions leading to global climate change, air pollution, and environmental degradation [4], [9]–[13]. Given the decreasing availability of fossil fuels and increasing environmental impacts, many countries have developed long-term sustainable energy plans. These plans include objectives to reduce dependence on fossil fuels, improve energy efficiency, and promote the use of renewable energy sources. Biodiesel is an example of how Indonesia, along with other countries, is striving to reduce its reliance on fossil fuels and move toward more sustainable and environmentally-friendly energy sources [14]–[17]. Through policies, innovation, and investments, biodiesel has become a significant choice in Indonesia's energy diversification efforts [18].

Biodiesel consumption worldwide, including in Indonesia, has experienced significant annual growth. This increase is in line with the growing number of vehicles and efforts to reduce dependence on fossil fuels [18]–[20]. However, the main issue in biodiesel production is that during the transesterification reaction to convert vegetable oil or fats into biodiesel, glycerol is also produced as a byproduct [19], [21]–[23]. Most biodiesel production methods generate glycerol in approximately 10% by weight of the biodiesel produced, meaning that for every 100 kg of biodiesel produced, 10 kg of glycerol is also generated [22], [24], [25]. According to previous researchers, the glycerol market is highly responsive to the increasing availability of glycerol in the market [22], [26], [27]. Furthermore, waste glycerol from biodiesel production can pose environmental pollution problems if not addressed. Hence, numerous research and industrial efforts are focused on developing ways to utilize and purify the generated glycerol, as well as exploring various applications for glycerol to prevent it from becoming waste. These reasons have drawn the attention of researchers to develop technologies to utilize glycerol, including its conversion into valuable energy products [14], [28]–[30].

Glycerol, also known as glycerin or 1,2,3-propanetriol, is a three-carbon molecule with a hydroxyl group on each carbon. It can be easily modified by reacting with the hydroxyl (-OH) groups [31]. The glycerol referred to in this article is the main byproduct of the transesterification reaction of fats or vegetable oils, such as sunflower oil, peanut oil, olive oil, soybean oil (in the United States) [32], [33], rapeseed oil, sunflower oil (in Europe) [34], palm oil in Southeast Asia (primarily Malaysia and Indonesia) [35]–[37], and coconut oil (in the Philippines) [38], to produce biodiesel.

Recently, the interest of researchers in the conversion of biomass into bioethanol as an energy product through fermentation has increased [39]–[42]. This is due to the sustainability and efficiency potential of this process in bioethanol production. Bioethanol is an alternative fuel produced from renewable sources, namely carbon-containing materials such as sugar or biomass. Glycerol, as one of the biomass sources, has an advantage because it contains a carbon source that can be directly converted into ethanol by specific microorganisms [23], [30], [43]–[46]. This allows for bypassing the hydrolysis step required by some other feedstocks sourced from lignocellulosic biomass in the second generation [40], [47]. Using glycerol as a feedstock is expected to reduce the reaction time needed to produce bioethanol. This can enhance production efficiency and reduce overall costs. The use of glycerol as a feedstock can also

result in a higher yield, meaning that more bioethanol can be produced from a given amount of glycerol [25], [31], [48].

Unfortunately, one of the challenges faced in using glycerol from biodiesel waste is its initial purity. Glycerol from biodiesel waste tends to have low purity, ranging from 40 to 55% by weight [39], [49]. To make this glycerol suitable for bioethanol production, a purification process is required such as distillation, chemical treatment, and membrane filtration or ion exchange. Glycerol can be purified from other contaminants like water, methanol, and catalytic salts using various purification techniques, including distillation, chemical treatment, membrane technology, and ion-exchange [50], [51]. Distillation is one of the commonly used methods to separate glycerol from other components [52]. Chemical treatment may involve chemical reactions to eliminate contaminants [53]. Membrane technology and ion-exchange involve the use of membranes and ion-exchange resins to separate glycerol from contaminants [50], [52]. After the purification process, glycerol can achieve a much higher purity, typically around 90 to 95% by weight. Higher purity allows this glycerol to be used more efficiently in bioethanol production.

Methodology


The method used in this study is a comprehensive literature review that involves extensive and in-depth research on the potential of crude glycerol from biodiesel production waste as a raw material for bioethanol especially in the purification of glycerol. A wide-ranging and diverse array of information sources includes research reports, conference proceedings, and relevant scientific articles, including those related to the purification of crude glycerol.

Potential of Crude Glycerol

The transesterification of vegetable or animal fats is a crucial chemical process employed in the production of biodiesel, a highly sought-after fuel for several compelling reasons. Biodiesel's appeal stems from its renewable nature, which contributes to reducing our reliance on finite fossil fuel resources [54], [55]. Moreover, biodiesel is celebrated for its environmentally friendly attributes, as it significantly reduces greenhouse gas emissions and air pollutants when compared to traditional petroleum-based fuels [56]–[59]. Additionally, biodiesel is known for its low toxicity, making it a safer and less hazardous option for both human health and the environment [60], [61].

This intricate process involves the transformation of vegetable or animal fats into biodiesel through a series of transesterification reactions. These reactions typically involve the use of alcohols, with methanol or ethanol being the common choices [20]. During this process, the triglycerides present in the fats are chemically modified to produce biodiesel, while the byproduct of this transformation is glycerol [62]. Glycerol is produced as a co-product, with its volume accounting for approximately 10% of the total biodiesel production [22], as illustrated in Figure 1[63], [64].

The generation of glycerol as a co-product is an integral aspect of biodiesel production, and the effective management and utilization of this glycerol co-product have garnered considerable attention in recent years [22], [26], [62]. This attention has primarily revolved around exploring ways to maximize the value of glycerol, not only as an integral part of the biodiesel production process but also as a valuable resource for various other applications, including its potential role as a precursor in the production of bioethanol. The strategic management of glycerol co-product opens up new avenues for achieving sustainability in the biodiesel production process and reinforces its position as a pivotal player in the transition towards cleaner and more environmentally responsible energy solutions [65].



Figure

1. Transesterification Reaction Scheme [66]

Purified glycerol presents a promising opportunity to play a pivotal role in a wide array of energy conversion processes. Its versatility enables the diversification of feedstock utilization derived from glycerol, thus unlocking the full spectrum of its advantages. By incorporating purified glycerol into various energy conversion processes, we embrace a sustainable and efficient approach to waste management and resource utilization. This approach is not only environmentally responsible but also economically viable [49].

The utilization of purified glycerol in diverse energy conversion processes signifies a concerted effort to transition towards cleaner and more sustainable energy sources. It acts as a testament to our commitment to addressing global challenges related to emissions and environmental impacts [67], [68]. The positive contributions of purified glycerol extend beyond energy production, reaching towards a broader vision of a greener and more sustainable future. Figure 2 [31] provides a visual representation of the numerous energy products that can be harnessed from glycerol, further underscoring its significance in our journey towards a cleaner and more eco-friendly energy landscape [69].




Figure 2. Diagram of Glycerol Conversion Pathway into Various Energy Products [31]

As previously elucidated, the production of glycerol has experienced a significant surge, primarily driven by the ever-increasing global production of biodiesel [70]. This surge is intrinsically linked to the continual expansion of biodiesel production capacity, which, in turn, results in a substantial upswing in the production of crude glycerol. To put this into perspective, by the year 2020, the production of crude glycerol had reached an impressive figure of approximately 5.8 billion pounds, a fact that is visually represented in Figure 3 as outlined in the study conducted by [69].




Figure 3. Global biodiesel and crude glycerol production from 2003 to 2020[69]

The consistent and upward trajectory of glycerol production is not without its challenges. One of the foremost challenges stems from the potential accumulation of surplus glycerol, which can pose logistical and environmental concerns if not effectively managed [49]. It is therefore imperative to explore strategies for the purposeful utilization or management of this surplus glycerol, and one such strategy is the conversion of glycerol into alternative products, with bioethanol emerging as a promising option [71]. This multifaceted approach not only addresses the challenge of glycerol surplus but also aligns with the broader goals of sustainability and resource optimization, offering a tangible solution to the burgeoning biodiesel industry's byproduct challenge.

Distillation Method

The distillation method is one of the techniques employed in the purification of crude glycerol (CG), which is a byproduct in biodiesel production [52], [72]. Distillation is a process for separating components within a mixture based on their differences in boiling points. In the case of purifying crude glycerol, distillation is used to separate glycerol from other substances that may be present in the mixture, such as water, methanol, catalytic salts, and other impurities. The following are the stages of the distillation method in the purification of crude glycerol from biodiesel production waste:

The stage of crude glycerol preparation: Before distillation, crude glycerol needs to be prepared. This may involve filtration or coarse separation to remove coarse particles or other solid substances that may be present in crude glycerol [24]. Simple distillation stage: This stage is used to remove components with lower boiling points, such as methanol. It is done by heating crude glycerol in a closed container. As the mixture is heated, the methanol component will evaporate earlier and then condense back into a liquid form [26], [73]. Fractionation stage: In this stage, glycerol components with higher boiling points will settle at the bottom of the column, while water components will evaporate to the top of the column and then condense back into liquid [74]. Purification stage: After distillation is completed, the fraction containing pure glycerol can be separated from other unwanted components, such as water and catalytic salts [20]. This stage may use separation equipment, such as centrifugation or filtration, to remove precipitates or other solid substances that may be present in the mixture. In addition, deionization or desalination can also be used to remove impurity ions or remaining salts in pure

glycerol. The distillation method generally produces glycerol with a purity of about 95% or higher [51].

Chemical Treatment Method

The chemical treatment method represents yet another viable approach for refining crude glycerol (CG), a byproduct stemming from biodiesel production [53]. In this method, specific chemicals are deployed to eliminate impurities and yield a purer form of glycerol. Notably, chemicals like sulfuric acid or phosphoric acid are introduced into the crude glycerol [75]. These chemicals initiate interactions with the impurities present, giving rise to compounds that can be readily separated. To elaborate further, during the chemical reaction, the impurities engage with the chemicals and form intricate compounds that can be precipitated. The resultant precipitate is subsequently separated through the utilization of a centrifuge or filtration process [76]–[78].

By employing the chemical treatment method, it is conceivable to achieve glycerol purities typically ranging from 90% to 95% [21], [79]. This method underscores the significance of chemical processes in enhancing the quality of glycerol derived from biodiesel production, paving the way for a variety of valuable applications while effectively addressing the challenges associated with impurity removal.

Membrane and Ion-Exchange Methods

The utilization of membrane technology in conjunction with the ion exchange method represents a highly effective approach to purifying crude glycerol (CG), an inevitable byproduct in the biodiesel production process [26], [77]. This combined approach offers a versatile means of eliminating a diverse range of impurities that may be present in crude glycerol. These impurities encompass substances like salts, ions, and undesirable organic compounds. The synergy between membrane technology and ion exchange techniques allows for the comprehensive removal of these unwanted elements, resulting in a significantly enhanced level of glycerol purity. This refined glycerol can subsequently be harnessed for various valuable applications, making it a valuable resource derived from biodiesel production [80], [81].

Membrane technology is a versatile method employed to separate molecules based on their respective size, charge, or physical characteristics. When it comes to purifying CG, specific membranes are designed to selectively remove various impurities from glycerol [50], [52], [53]. For example, ultrafiltration membranes are used to effectively eliminate solid particles and large molecules, while nanofiltration membranes come into play when the objective is to remove salts and small organic compounds. The process of separation through membrane technology offers a spectrum of glycerol purities, contingent upon the particular type of membrane employed. Ultrafiltration membranes generally yield glycerol with purities in the range of approximately 90% to 95% [82], while nanofiltration membranes can achieve purities surpassing 95% [83], [84]. This adaptability makes membrane technology an invaluable tool in refining crude glycerol and enhancing its usability in various applications.

The ion exchange process is a technique that employs specific resins or ion exchange materials with the ability to capture and replace particular ions present in crude glycerol (CG). This process is invaluable for eliminating undesired salts and ions effectively. Cation exchange resins are typically utilized to eliminate positively charged ions (cations), while anion exchange resins are used to remove negatively charged ions (anions) [81].

During ion exchange, the resins or materials function as selective traps for the targeted ions. As the CG is passed through these materials, the undesirable ions are captured and

exchanged for other ions that are less problematic or are more easily separated. This process significantly enhances the purity of glycerol, often achieving levels exceeding 95% [75]. Consequently, glycerol refined through the ion exchange method becomes highly suitable for a wide range of applications, particularly those that require stringent purity standards. It is an efficient and reliable approach to improve the quality of crude glycerol for diverse industrial and commercial purposes [85].

Bioethanol

Bioethanol is a renewable source of energy because its raw material can be naturally replenished through agriculture. This is a primary advantage in efforts to reduce dependence on fossil fuels and lower carbon emissions [55]. Bioethanol is used as a fuel for motor vehicles, particularly when blended with gasoline [86]. The mixture of bioethanol with gasoline is often referred to as E10 (10% bioethanol) or E85 (85% bioethanol), depending on the percentage of ethanol in the blend [87].

Bioethanol is produced from the fermentation of biomass involving a biochemical process in which microorganisms such as yeast or bacteria convert the sugars and carbohydrates present in biomass into ethanol (bioethanol) and carbon dioxide [88], [89]. Various microorganisms from fungi and bacteria can be used to convert sugars into ethanol. *Saccharomyces cerevisiae* (yeast) is the most commonly used fungus [90], [91], while bacteria that can be used include *Zymomonas mobilis*, *Escherichia coli* (*E. coli*), and *Kluyveromyces* spp [44], [46], [92]. Then, ethanol as the fermentation product can be separated and purified through the distillation process [52]. The choice of the right microorganism depends on the source of sugar to be converted into ethanol, as well as industrial needs and sustainability considerations. Some microorganisms have higher tolerance to alcohol or acidity, while others have a better capacity to convert specific types of sugars. Therefore, in bioethanol production, the selection of microorganisms is crucial for optimizing yield and efficiency [43].

Several challenges are associated with bioethanol production, particularly in terms of competition with food production, land use, and the sustainability of feedstock sources [93]. However, the utilization of glycerol (CG) as a feedstock originating from biodiesel production waste can be one of the solutions to address some of these challenges. By using glycerol from biodiesel production waste as a feedstock, there is no need for additional land or resources that would compete with food production [69]. The utilization of glycerol from biodiesel production waste is an example of how the renewable energy industry can integrate waste from one production process into a feedstock for another, creating more sustainable and environmentally friendly solutions. This approach can also help reduce environmental impacts and enhance efficiency within the renewable energy production chain [93].

Up to now, the production of bioethanol derived from first to third-generation biomass has developed and varies depending on location, technology, and resources used. Production of bioethanol from first-generation biomass, such as sugarcane, corn, and wheat, can reach around 60-70 billion liters per year worldwide [93], [94]. Some countries like the United States, Brazil, and Europe have become major producers of bioethanol from these first-generation sources. Meanwhile, the production of bioethanol from second-generation biomass, such as straw, wood, and algae, has faced many challenges in development, and the production volume is lower than the first generation, approximately 5-10 billion liters per year worldwide [94]. Furthermore, third-generation biomass, including algae and marine plants, is still in early stages of research and development, and its production is currently limited. Even the production of bioethanol from fourth-generation biomass is still in early research and development stages and has not yet reached significant commercial production levels [95]. Fourth-generation bioethanol development plans are a more recent concept that includes the utilization of CG. The technology is designed with genetic engineering techniques to enhance productivity and

efficiency in bioethanol production. Sources of biomass from various generations are presented in Table 1.

Table 1. Sources of biomass from various generations

Biomass Sources	wt. %			References
	Cellulose	Hemicelluloses	Lignin	
Wood	35-50	20-30	25-30	[96]
Straw	33-40	20-25	15-20	[97]
Sugarcane Bagasse	19-24	32-48	23-32	[98]
Corn cob	50.5	31	15	[99]
Scrap paper	60-70	10-20	5-10	[100]
Leaf	15-20	80-85	-	[101]
Algae	13-14	14-15	14	[32]

Conclusion

The global push towards renewable energy sources has underscored the important role of biodiesel production in replacing fossil fuels. However, the surge in production of the by-product glycerol poses a major challenge. This study has investigated the potential for the transformation of glycerol from biodiesel production into a raw material for bioethanol production. By strategically optimizing the fermentation process and utilizing purification technologies such as distillation, chemical treatment, and membrane filtration, glycerol can be efficiently converted into bioethanol. The important progress achieved in increasing the purity of crude glycerol (CG) from 50% to approximately 90–95 wt.% further emphasizes the feasibility and opportunities of this approach.

The conversion of glycerol to bioethanol is emerging as a promising step towards achieving a more sustainable and environmentally friendly renewable energy landscape. The comprehensive integration of purification methods, advances in genetic engineering, and effective utilization of glycerol as a bioethanol feedstock marks a significant step in overcoming the challenges associated with managing glycerol byproducts. Thus, the potential for glycerol conversion has become a hope for more environmentally friendly energy solutions.

Acknowledgment

I want to express my heartfelt gratitude to the Directorate of Research, Technology, and Community Engagement, Directorate General of Higher Education, Research, and Technology. The support and training in scientific article writing provided have been a strong foundation for us in carrying out various programs and projects aimed at promoting research, innovation, and technology development.

REFERENCES

- [1] D. P. Macedo and A. C. Marques, "Is the energy transition ready for declining budgets in RD&D for fossil fuels? Evidence from a panel of European countries," *J Clean Prod*, vol. 417, p. 138102, Sep. 2023, doi: 10.1016/j.jclepro.2023.138102.
- [2] N. Uusitalo, "Coming off fossil fuels: Visual recollection of fossil fuel dependency," *Vis Stud*, vol. 37, no. 3, pp. 184–192, May 2022, doi: 10.1080/1472586X.2022.2090124.
- [3] Z. Todd, "Fossil Fuels and Fossil Kin: An Environmental Kin Study of Weaponised Fossil Kin and Alberta's <sc>So-Called</sc> 'Energy Resources Heritage,'" *Antipode*, Nov. 2022, doi: 10.1111/anti.12897.
- [4] L. Hermwille and L. Sanderink, "Make Fossil Fuels Great Again? The Paris Agreement, Trump, and the US Fossil Fuel Industry," *Glob Environ Polit*, vol. 19, no. 4, pp. 45–62, Nov. 2019, doi: 10.1162/glep_a_00526.

- [5] S. A. Neves and A. C. Marques, “The substitution of fossil fuels in the US transportation energy mix: Are emissions decoupling from economic growth?,” *Research in Transportation Economics*, vol. 90, p. 101036, Dec. 2021, doi: 10.1016/j.retrec.2021.101036.
- [6] G. Giacosa and T. R. Walker, “A policy perspective on Nova Scotia’s plans to reduce dependency on fossil fuels for electricity generation and improve air quality,” *Cleaner Production Letters*, vol. 3, p. 100017, Dec. 2022, doi: 10.1016/j.clpl.2022.100017.
- [7] G. A. Ryabov, “Cofiring of Coal and Fossil Fuels is a Way to Decarbonization of Heat and Electricity Generation (Review),” *Thermal Engineering*, vol. 69, no. 6, pp. 405–417, Jun. 2022, doi: 10.1134/S0040601522060052.
- [8] A. C. Ozdemir, “Decomposition and decoupling analysis of carbon dioxide emissions in electricity generation by primary fossil fuels in Turkey,” *Energy*, vol. 273, p. 127264, Jun. 2023, doi: 10.1016/j.energy.2023.127264.
- [9] M. K. Anser, I. Hanif, M. Alharthi, and I. S. Chaudhry, “Impact of fossil fuels, renewable energy consumption and industrial growth on carbon emissions in Latin American and Caribbean economies,” *Atmósfera*, Jul. 2020, doi: 10.20937/ATM.52732.
- [10] G. Zimon *et al.*, “The Impact of Fossil Fuels, Renewable Energy, and Nuclear Energy on South Korea’s Environment Based on the STIRPAT Model: ARDL, FMOLS, and CCR Approaches,” *Energies (Basel)*, vol. 16, no. 17, p. 6198, Aug. 2023, doi: 10.3390/en16176198.
- [11] X. Li, “How can we make an orderly transition away from fossil fuels? A global tour of modern energy,” *Energy & Environment*, p. 0958305X2311613, Mar. 2023, doi: 10.1177/0958305X231161300.
- [12] D. Steel, P. Bartha, and R. Cripps, “Climate Precaution and Producer versus Consumer Dependence on Fossil Fuels,” *Ethics Policy Environ*, pp. 1–25, Aug. 2023, doi: 10.1080/21550085.2023.2247815.
- [13] D. A. Netreba, V. S. Kovaleva, D. V. Smolyanova, M. O. Belyaev, D. A. Shlygin, and M. V. Shershulina, “Problem and The Riphean Deposits Hydrocarbon Potential of The Republic of Bashkortostan,” *Geology, Geophysics and Development of Oil and Gas Fields*, no. 4, pp. 5–17, 2023, doi: 10.33285/2413-5011-2023-4(376)-5-17.
- [14] A. R. Zahedi and S. A. Mirnezami, “Experimental analysis of biomass to biodiesel conversion using a novel renewable combined cycle system,” *Renew Energy*, vol. 162, pp. 1177–1194, Dec. 2020, doi: 10.1016/j.renene.2020.08.071.
- [15] T. Barreiros, A. Young, R. Cavalcante, and E. Queiroz, “Impact of biodiesel production on a soybean biorefinery,” *Renew Energy*, vol. 159, pp. 1066–1083, Oct. 2020, doi: 10.1016/j.renene.2020.06.064.
- [16] K. R. Szulczyk and R. A. Badeeb, “Nontraditional sources for biodiesel production in Malaysia: The economic evaluation of hemp, jatropha, and kenaf biodiesel,” *Renew Energy*, vol. 192, pp. 759–768, Jun. 2022, doi: 10.1016/j.renene.2022.04.097.
- [17] A. Halimatussadiah, D. Nainggolan, S. Yui, F. R. Moeis, and A. A. Siregar, “Progressive biodiesel policy in Indonesia: Does the Government’s economic proposition hold?,” *Renewable and Sustainable Energy Reviews*, vol. 150, p. 111431, Oct. 2021, doi: 10.1016/j.rser.2021.111431.
- [18] C. Fischer and T. Meyer, “Baptists and Bootleggers in the Biodiesel Trade: Eu-Biodiesel (Indonesia),” *SSRN Electronic Journal*, 2019, doi: 10.2139/ssrn.3489187.
- [19] T. M. Y. Khan, “Direct Transesterification for Biodiesel Production and Testing the Engine for Performance and Emissions Run on Biodiesel-Diesel-Nano Blends,” *Nanomaterials*, vol. 11, no. 2, p. 417, Feb. 2021, doi: 10.3390/nano11020417.
- [20] I. O. Akpan, I. Edeh, and L. Uyigue, “A Review on Biodiesel Production,” *Petro Chem Indus Intern*, vol. 6, no. 2, pp. 131–141, 2023.

- [21] A. R. Velez, J. R. Mufari, and L. J. Rovetto, “Sodium salts solubility in ternary glycerol+water+alcohol mixtures present in purification process of crude glycerol from the biodiesel industry,” *Fluid Phase Equilib*, vol. 497, pp. 55–63, Oct. 2019, doi: 10.1016/j.fluid.2019.05.023.
- [22] Y. Liu, B. Zhong, and A. Lawal, “Recovery and utilization of crude glycerol, a biodiesel byproduct,” *RSC Adv*, vol. 12, no. 43, pp. 27997–28008, 2022, doi: 10.1039/D2RA05090K.
- [23] F. Zhao, Y. Wu, Q. Wang, M. Zheng, and Q. Cui, “Glycerol or crude glycerol as substrates make *Pseudomonas aeruginosa* achieve anaerobic production of rhamnolipids,” *Microb Cell Fact*, vol. 20, no. 1, p. 185, Dec. 2021, doi: 10.1186/s12934-021-01676-2.
- [24] L. R. Kumar, S. K. Yellapu, R. D. Tyagi, and X. Zhang, “A review on variation in crude glycerol composition, bio-valorization of crude and purified glycerol as carbon source for lipid production,” *Bioresour Technol*, vol. 293, p. 122155, Dec. 2019, doi: 10.1016/j.biortech.2019.122155.
- [25] C. R. Chilakamaray, A. M. Mimi Sakinah, A. W. Zularism, I. A. Khilji, and S. Kumarasamy, “Glycerol Waste to Bio-Ethanol: Optimization of Fermentation Parameters by the Taguchi Method,” *J Chem*, vol. 2022, pp. 1–11, Oct. 2022, doi: 10.1155/2022/4892992.
- [26] T. Attarbach, M. D. Kingsley, and V. Spallina, “New trends on crude glycerol purification: A review,” *Fuel*, vol. 340, p. 127485, May 2023, doi: 10.1016/j.fuel.2023.127485.
- [27] V. Naranje, R. Swarnalatha, O. Batra, and S. Salunkhe, “Technological Assessment on Steam Reforming Process of Crude Glycerol to Produce Hydrogen in an Integrated Waste Cooking-Oil-Based Biodiesel Production Scenario,” *Processes*, vol. 10, no. 12, p. 2670, Dec. 2022, doi: 10.3390/pr10122670.
- [28] R. Pothu, N. Mamed, R. Boddula, H. Mitta, V. Perugopu, and N. Al-Qahtani, “Sustainable conversion of biodiesel-waste glycerol to acrolein over Pd-modified mesoporous catalysts,” *Mater Sci Energy Technol*, vol. 6, pp. 226–236, 2023, doi: 10.1016/j.mset.2022.12.012.
- [29] G. Chemiru and G. Gonfa, “Preparation and characterization of glycerol plasticized yam starch-based films reinforced with titanium dioxide nanofiller,” *Carbohydrate Polymer Technologies and Applications*, vol. 5, p. 100300, Jun. 2023, doi: 10.1016/j.carpta.2023.100300.
- [30] J. Pradima, M. R. Kulkarni, and Archana, “Review on enzymatic synthesis of value added products of glycerol, a by-product derived from biodiesel production,” *Resource-Efficient Technologies*, vol. 3, no. 4, pp. 394–405, Dec. 2017, doi: 10.1016/j.reffit.2017.02.009.
- [31] Q. (Sophia) He, J. McNutt, and J. Yang, “Utilization of the residual glycerol from biodiesel production for renewable energy generation,” *Renewable and Sustainable Energy Reviews*, vol. 71, pp. 63–76, May 2017, doi: 10.1016/j.rser.2016.12.110.
- [32] M. Fazil Khan, A. Garg, S. Jain, G. Dwivedi, and T. Nath Verma, “Optimization of low-temperature transesterification of low FFA blend of sunflower oil and algae oil,” *Fuel*, vol. 279, p. 118459, Nov. 2020, doi: 10.1016/j.fuel.2020.118459.
- [33] C. S. Osorio-González, N. Gómez-Falcon, F. Sandoval-Salas, R. Saini, S. K. Brar, and A. A. Ramírez, “Production of Biodiesel from Castor Oil: A Review,” *Energies (Basel)*, vol. 13, no. 10, p. 2467, May 2020, doi: 10.3390/en13102467.
- [34] V. Makarevičienė and I. Sendžikaitė, “Biocatalytic transesterification of rapeseed oil by methyl formate,” *Žemės ūkio mokslai*, vol. 26, no. 1, May 2019, doi: 10.6001/zemesukiomokslai.v26i1.3969.

- [35] M. K. Lam, N. A. Jamalluddin, and K. T. Lee, “Production of Biodiesel Using Palm Oil,” in *Biofuels: Alternative Feedstocks and Conversion Processes for the Production of Liquid and Gaseous Biofuels*, Elsevier, 2019, pp. 539–574. doi: 10.1016/B978-0-12-816856-1.00023-3.
- [36] A. Soly Peter *et al.*, “Optimization of biodiesel production by transesterification of palm oil and evaluation of biodiesel quality,” *Mater Today Proc*, vol. 42, pp. 1002–1007, 2021, doi: 10.1016/j.matpr.2020.11.995.
- [37] Nur Aishah Rajali, Salina Mat Radzi, Maryam Mohamed Rehan, and Nur Amalina Mohd Amin, “Optimization of the Biodiesel Production via Transesterification Reaction of Palm Oil using Response Surface Methodology (RSM): A Review,” *Malaysian Journal of Science Health & Technology*, vol. 8, no. 2, pp. 58–67, Sep. 2022, doi: 10.33102/mjosht.v8i2.292.
- [38] S. Boangmanalu and E. Ginting, “Comparison between Transesterification Reaction with Microwave Heating and Conventional Heating for Biodiesel Production from Coconut Oil with Alkaline Catalyst,” *Indonesian Journal of Chemical Science and Technology (IJCST)*, vol. 6, no. 2, p. 106, Jul. 2023, doi: 10.24114/ijcst.v6i2.49364.
- [39] S. H. Mohd Azhar *et al.*, “Yeasts in sustainable bioethanol production: A review,” *Biochemistry and Biophysics Reports*, vol. 10. Elsevier B.V., pp. 52–61, Jul. 01, 2017. doi: 10.1016/j.bbrep.2017.03.003.
- [40] H. Chen and X. Fu, “Industrial technologies for bioethanol production from lignocellulosic biomass,” *Renewable and Sustainable Energy Reviews*, vol. 57, pp. 468–478, May 2016, doi: 10.1016/j.rser.2015.12.069.
- [41] A. P. Jacobus, J. Gross, J. H. Evans, S. R. Ceccato-Antonini, and A. K. Gombert, “*Saccharomyces cerevisiae* strains used industrially for bioethanol production,” *Essays Biochem*, vol. 65, no. 2, Jul. 2021, doi: 10.1042/EBC20200160.
- [42] J. Zhang, A. Rentizelas, X. Zhang, and J. Li, “Sustainable production of lignocellulosic bioethanol towards zero waste biorefinery,” *Sustainable Energy Technologies and Assessments*, vol. 53, p. 102627, Oct. 2022, doi: 10.1016/j.seta.2022.102627.
- [43] J. M. Clomburg and R. Gonzalez, “Anaerobic fermentation of glycerol: a platform for renewable fuels and chemicals,” *Trends Biotechnol*, vol. 31, no. 1, pp. 20–28, Jan. 2013, doi: 10.1016/j.tibtech.2012.10.006.
- [44] G. Bagnato, A. Iulianelli, A. Sanna, and A. Basile, “Glycerol Production and Transformation: A Critical Review with Particular Emphasis on Glycerol Reforming Reaction for Producing Hydrogen in Conventional and Membrane Reactors,” *Membranes (Basel)*, vol. 7, no. 2, p. 17, Mar. 2017, doi: 10.3390/membranes7020017.
- [45] N. Stepanov and E. Efremenko, “Immobilised cells of *Pachysolen tannophilus* yeast for ethanol production from crude glycerol,” *N Biotechnol*, vol. 34, pp. 54–58, Jan. 2017, doi: 10.1016/j.nbt.2016.05.002.
- [46] O. Cofré, M. Ramírez, J. M. Gómez, and D. Cantero, “Optimization of culture media for ethanol production from glycerol by *Escherichia coli*,” *Biomass Bioenergy*, vol. 37, pp. 275–281, Feb. 2012, doi: 10.1016/j.biombioe.2011.12.002.
- [47] P. B. Subhedar and P. R. Gogate, “Intensification of enzymatic hydrolysis of lignocellulose using ultrasound for efficient bioethanol production: A review,” *Industrial and Engineering Chemistry Research*, vol. 52, no. 34, pp. 11816–11828, Aug. 28, 2013. doi: 10.1021/ie401286z.
- [48] M. Raza, A. Inayat, and B. Abu-Jdayil, “Crude Glycerol as a Potential Feedstock for Future Energy via Thermochemical Conversion Processes: A Review,” *Sustainability*, vol. 13, no. 22, p. 12813, Nov. 2021, doi: 10.3390/su132212813.

- [49] A. Malaika, K. Ptaszyńska, and M. Kozłowski, “Conversion of renewable feedstock to bio-carbons dedicated for the production of green fuel additives from glycerol,” *Fuel*, vol. 288, p. 119609, Mar. 2021, doi: 10.1016/j.fuel.2020.119609.
- [50] W. De Schepper, M. D. Moraru, B. Jacobs, M. Oudshoorn, and J. Helsen, “Electrodialysis of aqueous NaCl-glycerol solutions: A phenomenological comparison of various ion exchange membranes,” *Sep Purif Technol*, vol. 217, pp. 274–283, Jun. 2019, doi: 10.1016/j.seppur.2019.02.030.
- [51] A. Anvari, A. Azimi Yancheshme, and A. Ronen, “Enhanced performance of membrane distillation using radio-frequency induction heated thermally conducting feed spacers,” *Sep Purif Technol*, vol. 250, p. 117276, Nov. 2020, doi: 10.1016/j.seppur.2020.117276.
- [52] K. Zhang, Y. Qin, F. He, J. Liu, Y. Zhang, and L. Liu, “Concentration of aqueous glycerol solution by using continuous-effect membrane distillation,” *Sep Purif Technol*, vol. 144, pp. 186–196, Apr. 2015, doi: 10.1016/j.seppur.2015.02.034.
- [53] R. Dhabhai, E. Ahmadifeijani, A. K. Dalai, and M. Reaney, “Purification of crude glycerol using a sequential physico-chemical treatment, membrane filtration, and activated charcoal adsorption,” *Sep Purif Technol*, vol. 168, pp. 101–106, Aug. 2016, doi: 10.1016/j.seppur.2016.05.030.
- [54] U. Lawan Muhammad, “Biofuels as the Starring Substitute to Fossil Fuels,” *Petroleum Science and Engineering*, vol. 2, no. 1, p. 44, 2018, doi: 10.11648/j.pse.20180201.17.
- [55] F. A. Malla, S. A. Bandh, S. A. Wani, A. T. Hoang, and N. A. Sofi, “Biofuels: Potential Alternatives to Fossil Fuels,” in *Biofuels in Circular Economy*, Singapore: Springer Nature Singapore, 2022, pp. 1–15. doi: 10.1007/978-981-19-5837-3_1.
- [56] R. Johansson, S. Meyer, J. Whistance, W. Thompson, and D. Debnath, “Greenhouse gas emission reduction and cost from the United States biofuels mandate,” *Renewable and Sustainable Energy Reviews*, vol. 119, p. 109513, Mar. 2020, doi: 10.1016/j.rser.2019.109513.
- [57] N. Mahbub, E. Gemechu, H. Zhang, and A. Kumar, “The life cycle greenhouse gas emission benefits from alternative uses of biofuel coproducts,” *Sustainable Energy Technologies and Assessments*, vol. 34, pp. 173–186, Aug. 2019, doi: 10.1016/j.seta.2019.05.001.
- [58] H. Xu, L. Ou, Y. Li, T. R. Hawkins, and M. Wang, “Life Cycle Greenhouse Gas Emissions of Biodiesel and Renewable Diesel Production in the United States,” *Environ Sci Technol*, vol. 56, no. 12, pp. 7512–7521, Jun. 2022, doi: 10.1021/acs.est.2c00289.
- [59] Z. Islam Rony *et al.*, “Alternative fuels to reduce greenhouse gas emissions from marine transport and promote UN sustainable development goals,” *Fuel*, vol. 338, p. 127220, Apr. 2023, doi: 10.1016/j.fuel.2022.127220.
- [60] K. R. Landwehr *et al.*, “Biodiesel feedstock determines exhaust toxicity in 20% biodiesel: 80% mineral diesel blends,” *Chemosphere*, vol. 310, p. 136873, Jan. 2023, doi: 10.1016/j.chemosphere.2022.136873.
- [61] N. Yilmaz, F. M. Vigil, and B. Donaldson, “Fuel effects on PAH formation, toxicity and regulated pollutants: Detailed comparison of biodiesel blends with propanol, butanol and pentanol,” *Science of The Total Environment*, vol. 849, p. 157839, Nov. 2022, doi: 10.1016/j.scitotenv.2022.157839.
- [62] S. Marx, “Glycerol-free biodiesel production through transesterification: a review,” *Fuel Processing Technology*, vol. 151, pp. 139–147, Oct. 2016, doi: 10.1016/j.fuproc.2016.05.033.
- [63] Y. Zhou, K. Li, and S. Sun, “Simultaneous esterification and transesterification of waste phoenix seed oil with a high free fatty acid content using a free lipase catalyst to prepare biodiesel,” *Biomass Bioenergy*, vol. 144, p. 105930, Jan. 2021, doi: 10.1016/j.biombioe.2020.105930.

- [64] H. Herliati, R. Yunus, U. Rashid, Z. Z. Abidin, and I. S. Ahamad, “Synthesis of 1,3-dichloropropanol from glycerol using muriatic acid as chlorinating agent,” *Asian Journal of Chemistry*, vol. 26, no. 10, 2014, doi: 10.14233/ajchem.2014.15995.
- [65] M. Zhang and H. Wu, “Effect of major impurities in crude glycerol on solubility and properties of glycerol/methanol/bio-oil blends,” *Fuel*, vol. 159, pp. 118–127, Nov. 2015, doi: 10.1016/j.fuel.2015.06.062.
- [66] M. E. Borges and L. Díaz, “Recent developments on heterogeneous catalysts for biodiesel production by oil esterification and transesterification reactions: A review,” *Renewable and Sustainable Energy Reviews*, vol. 16, no. 5, pp. 2839–2849, Jun. 2012, doi: 10.1016/j.rser.2012.01.071.
- [67] Q. (Sophia) He, J. McNutt, and J. Yang, “Utilization of the residual glycerol from biodiesel production for renewable energy generation,” *Renewable and Sustainable Energy Reviews*, vol. 71, pp. 63–76, May 2017, doi: 10.1016/j.rser.2016.12.110.
- [68] C. R. Chilakamarry *et al.*, “Bioconversion of Glycerol into Biofuels—Opportunities and Challenges,” *Bioenergy Res*, vol. 15, no. 1, pp. 46–61, Mar. 2022, doi: 10.1007/s12155-021-10353-6.
- [69] Y. Liu, B. Zhong, and A. Lawal, “Recovery and utilization of crude glycerol, a biodiesel byproduct,” *RSC Adv*, vol. 12, no. 43, pp. 27997–28008, 2022, doi: 10.1039/D2RA05090K.
- [70] S. Chozhavendhan, R. Praveen Kumar, S. Elavazhagan, B. Barathiraja, M. Jayakumar, and S. J. Varjani, “Utilization of Crude Glycerol from Biodiesel Industry for the Production of Value-Added Bioproducts,” 2018, pp. 65–82. doi: 10.1007/978-981-10-7431-8_4.
- [71] C. Sivasankaran, P. K. Ramanujam, B. Balasubramanian, and J. Mani, “Recent progress on transforming crude glycerol into high value chemicals: a critical review,” *Biofuels*, vol. 10, no. 3, pp. 309–314, May 2019, doi: 10.1080/17597269.2016.1174018.
- [72] Y. Xiao, G. Xiao, and A. Varma, “A Universal Procedure for Crude Glycerol Purification from Different Feedstocks in Biodiesel Production: Experimental and Simulation Study,” *Ind Eng Chem Res*, vol. 52, no. 39, pp. 14291–14296, Oct. 2013, doi: 10.1021/ie402003u.
- [73] C. R. Chilakamarry, A. M. Mimi Sakinah, A. W. Zularisam, A. Pandey, and D.-V. N. Vo, “Technological perspectives for utilisation of waste glycerol for the production of biofuels: A review,” *Environ Technol Innov*, vol. 24, p. 101902, Nov. 2021, doi: 10.1016/j.eti.2021.101902.
- [74] Irvan, B. Trisakti, R. Hasibuan, and M. Joli, “Fermentative utilization of glycerol residue for the production of acetic acid,” *IOP Conf Ser Mater Sci Eng*, vol. 309, no. 1, p. 012126, Feb. 2018, doi: 10.1088/1757-899X/309/1/012126.
- [75] C. G. Chol, R. Dhabhai, A. K. Dalai, and M. Reaney, “Purification of crude glycerol derived from biodiesel production process: Experimental studies and techno-economic analyses,” *Fuel Processing Technology*, vol. 178, pp. 78–87, Sep. 2018, doi: 10.1016/j.fuproc.2018.05.023.
- [76] V. Y. Mena-Cervantes, R. Hernández-Altamirano, and A. Tiscareño-Ferrer, “Development of a green one-step neutralization process for valorization of crude glycerol obtained from biodiesel,” *Environmental Science and Pollution Research*, vol. 27, no. 23, pp. 28500–28509, Aug. 2020, doi: 10.1007/s11356-019-07287-0.
- [77] O. S. Muniru, C. S. Ezeanyanaso, E. U. Akubueze, C. C. Igwe, and G. N. Elemo, “Review of Different Purification Techniques for Crude Glycerol from Biodiesel Production,” *Journal of Energy Research and Reviews*, pp. 1–6, Dec. 2018, doi: 10.9734/jenrr/2019/v2i129728.

- [78] M. Oliveira, A. Ramos, E. Monteiro, and A. Rouboa, "Improvement of the Crude Glycerol Purification Process Derived from Biodiesel Production Waste Sources through Computational Modeling," *Sustainability*, vol. 14, no. 3, p. 1747, Feb. 2022, doi: 10.3390/su14031747.
- [79] R. Dhabhai, P. Koranian, Q. Huang, D. S. B. Scheibelhoffer, and A. K. Dalai, "Purification of glycerol and its conversion to value-added chemicals: A review," *Sep Sci Technol*, vol. 58, no. 7, pp. 1383–1402, May 2023, doi: 10.1080/01496395.2023.2189054.
- [80] N. C, Y. K V, M. P. R, S. M, and G. B. R, "Simultaneous refining of biodiesel-derived crude glycerol and synthesis of value-added powdered catalysts for biodiesel production: A green chemistry approach for sustainable biodiesel industries," *J Clean Prod*, vol. 363, p. 132448, Aug. 2022, doi: 10.1016/j.jclepro.2022.132448.
- [81] A. P. Lopes, P. R. Souza, E. G. Bonafé, J. V. Visentainer, A. F. Martins, and E. A. Canesin, "Purified glycerol is produced from the frying oil transesterification by combining a pre-purification strategy performed with condensed tannin polymer derivative followed by ionic exchange," *Fuel Processing Technology*, vol. 187, pp. 73–83, May 2019, doi: 10.1016/j.fuproc.2019.01.014.
- [82] J. J. Torres, N. E. Rodriguez, J. T. Arana, N. A. Ochoa, J. Marchese, and C. Pagliero, "Ultrafiltration polymeric membranes for the purification of biodiesel from ethanol," *J Clean Prod*, vol. 141, pp. 641–647, Jan. 2017, doi: 10.1016/j.jclepro.2016.09.130.
- [83] T. D. Kusworo, W. Widayat, D. P. Utomo, Y. H. S. Pratama, and R. A. V. Arianti, "Performance evaluation of modified nanohybrid membrane polyethersulfone-nano ZnO (PES-nano ZnO) using three combination effect of PVP, irradiation of ultraviolet and thermal for biodiesel purification," *Renew Energy*, vol. 148, pp. 935–945, Apr. 2020, doi: 10.1016/j.renene.2019.10.177.
- [84] G. Dong *et al.*, "Free glycerol removal from monoglyceride using TiO₂-ZrO₂ nanofiltration membranes," *Sep Purif Technol*, vol. 224, pp. 366–372, Oct. 2019, doi: 10.1016/j.seppur.2019.05.043.
- [85] R. Shanmughom and S. K. Raghu, "Purification strategies for crude glycerol: A transesterification derivative," 2023, p. 020012. doi: 10.1063/5.0155313.
- [86] S.-R. Jhang, Y.-C. Lin, K.-S. Chen, S.-L. Lin, and S. Batterman, "Evaluation of fuel consumption, pollutant emissions and well-to-wheel GHGs assessment from a vehicle operation fueled with bioethanol, gasoline and hydrogen," *Energy*, vol. 209, p. 118436, Oct. 2020, doi: 10.1016/j.energy.2020.118436.
- [87] B. Sayin Kul and M. Ciniviz, "An evaluation based on energy and exergy analyses in SI engine fueled with waste bread bioethanol-gasoline blends," *Fuel*, vol. 286, p. 119375, Feb. 2021, doi: 10.1016/j.fuel.2020.119375.
- [88] J. Frankowski, A. Wawro, J. Batog, K. Szambelan, and A. Łacka, "Bioethanol Production Efficiency from Sorghum Waste Biomass," *Energies (Basel)*, vol. 15, no. 9, May 2022, doi: 10.3390/en15093132.
- [89] H. Rahman, A. Nehemia, and H. P. Astuti, "Investigating the potential of avocado seeds for bioethanol production: A study on boiled water delignification pretreatment," *International Journal of Renewable Energy Development*, vol. 12, no. 4, pp. 648–654, Jul. 2023, doi: 10.14710/ijred.2023.52532.
- [90] M. Ghazanfar *et al.*, "Bioethanol Production Optimization from KOH-Pretreated Bombax ceiba Using Saccharomyces cerevisiae through Response Surface Methodology," *Fermentation*, vol. 8, no. 4, p. 148, Mar. 2022, doi: 10.3390/fermentation8040148.

- [91] I. K. M. Yu *et al.*, “Tuneable functionalities in layered double hydroxide catalysts for thermochemical conversion of biomass-derived glucose to fructose,” *Chemical Engineering Journal*, vol. 383, p. 122914, Mar. 2020, doi: 10.1016/j.cej.2019.122914.
- [92] P. Godoy, A. Mourenza, S. Hernández-Romero, J. González-López, and M. Manzanera, “Microbial Production of Ethanol From Sludge Derived From an Urban Wastewater Treatment Plant,” *Front Microbiol*, vol. 9, Nov. 2018, doi: 10.3389/fmicb.2018.02634.
- [93] S. A. Haji Esmaeili, J. Szmerekovsky, A. Sobhani, A. Dybing, and T. O. Peterson, “Sustainable biomass supply chain network design with biomass switching incentives for first-generation bioethanol producers,” *Energy Policy*, vol. 138, p. 111222, Mar. 2020, doi: 10.1016/j.enpol.2019.111222.
- [94] S. A. Haji Esmaeili, A. Sobhani, J. Szmerekovsky, A. Dybing, and G. Pourhashem, “First-generation vs. second-generation: A market incentives analysis for bioethanol supply chains with carbon policies,” *Appl Energy*, vol. 277, p. 115606, Nov. 2020, doi: 10.1016/j.apenergy.2020.115606.
- [95] I. S. Tan, M. K. Lam, H. C. Y. Foo, S. Lim, and K. T. Lee, “Advances of macroalgae biomass for the third generation of bioethanol production,” *Chin J Chem Eng*, vol. 28, no. 2, pp. 502–517, Feb. 2020, doi: 10.1016/j.cjche.2019.05.012.
- [96] K. Robak and M. Balcerek, “Review of Second-Generation Bioethanol Production from Residual Biomass,” *Food Technol Biotechnol*, vol. 56, no. 2, 2018, doi: 10.17113/ftb.56.02.18.5428.
- [97] J. A. Ferreira, P. Brancoli, S. Agnihotri, K. Bolton, and M. J. Taherzadeh, “A review of integration strategies of lignocelluloses and other wastes in 1st generation bioethanol processes,” *Process Biochemistry*, vol. 75, pp. 173–186, Dec. 2018, doi: 10.1016/j.procbio.2018.09.006.
- [98] M. A. de Almeida and R. Colombo, “Production Chain of First-Generation Sugarcane Bioethanol: Characterization and Value-Added Application of Wastes,” *Bioenergy Res*, vol. 16, no. 2, pp. 924–939, Jun. 2023, doi: 10.1007/s12155-021-10301-4.
- [99] A. F. Murawski de Mello, L. Porto de Souza Vandenberghe, K. K. Valladares-Diestra, G. Amaro Bittencourt, W. J. Martinez Burgos, and C. R. Soccol, “Corn First-Generation Bioethanol Unities with Energy and Dried Grains with Solubles (DDGS) Production,” 2022, pp. 109–132. doi: 10.1007/978-3-031-01241-9_6.
- [100] M. Fantini, “Biomass Availability, Potential and Characteristics,” 2017, pp. 21–54. doi: 10.1007/978-3-319-48288-0_2.
- [101] G. Kildegaard, M. del P. Balbi, G. Salierno, M. Cassanello, C. De Blasio, and M. Galvagno, “A Cleaner Delignification of Urban Leaf Waste Biomass for Bioethanol Production, Optimised by Experimental Design,” *Processes*, vol. 10, no. 5, p. 943, May 2022, doi: 10.3390/pr10050943.